

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : **Oven & Grill**
 Product code : 0931

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Liquid Steam Cleaner

1.3. Details of the supplier of the safety data sheet

Crestek Cleaning Center, Inc.
 1161 Kapiolani Blvd.
 Honolulu, HI 96814
 T 1-(808) 942-2500

1.4. Emergency telephone number

Emergency number : CHEMTEL: 800-255-3924

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS US classification

Skin Corr. 1 H314
 Eye Dam. 1 H318

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms :



GHS05

Signal word :

Danger

Hazard statements :

Causes severe skin burns and eye damage.
 Causes serious eye damage.

Precautionary statements :

Do not breathe fume, mist, vapors.
 Wash hands and forearms thoroughly after handling.
 Wear eye protection, face protection, protective clothing, protective gloves.
 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Immediately call a poison center or doctor/physician.
 Specific treatment (see the emergency and first aid section of this Safety Data Sheet on this label).
 Wash contaminated clothing before reuse.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Hazard not otherwise classified (HNOC)

No additional information available.

2.4. Unknown acute toxicity (GHS US)

No data available

Oven & Grill

Safety Data Sheet

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable.

(NOTE: If component displays the * (asterisk) symbol, the following statement applies.)

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret.

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS US classification
sodium hydroxide	(CAS-No.) 1310-73-2	5 - 10	Met. Corr. 1, H290 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402
potassium hydroxide	(CAS-No.) 1310-58-3	1 - 5	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318
tetrasodium ethylenediaminetetracetate	(CAS-No.) 64-02-8	1 - 5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
polyethylene glycol mono(octylphenyl) ether phosphate	(CAS-No.) 52623-95-7	< 5	Skin Corr. 1C, H314 Eye Dam. 1, H318 STOT SE 3, H335 Asp. Tox. 1, H304

(NOTE: If component displays the * (asterisk) symbol, the following statement applies.)

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Corrosion of the upper respiratory tract. Respiratory difficulties.
Symptoms/effects after skin contact	: Causes burns/corrosion of the skin.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed. Abdominal pain. Difficulty in swallowing. Burns to the gastric/intestinal mucosa.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Extinguishing media for surrounding fires. All extinguishing media allowed.
Unsuitable extinguishing media	: No unsuitable extinguishing media known.

5.2. Special hazards arising from the substance or mixture

Reactivity	: Reacts violently with (some) acids: release of heat. Reacts with (some) metals and their compounds: release of highly flammable gases/vapors (hydrogen). Reacts with (some) halogen compounds. Reacts with (strong) oxidizers.
------------	--

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: No additional information available.

Oven & Grill

Safety Data Sheet

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

Protective equipment : Protective gloves.
Protective clothing.
Protective goggles.
Respiratory protection.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Plug the leak, cut off the supply. If reacting: dilute toxic gas/vapor with water spray.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Small quantities of liquid spill: neutralize with dilute acid solution. Wash down leftovers with plenty of water. Wash clothing and equipment after handling.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not get in eyes, on skin, or on clothing. Do not breathe fume, mist, vapors. Ensure good ventilation of the work station. Observe normal hygiene standards. Provide good ventilation in process area to prevent formation of vapor. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and forearms thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide local exhaust or general room ventilation. Comply with applicable regulations.

Incompatible products : Acids. Oxidizing agent.

Storage area : Store in a cool, dry well-ventilated area. Keep container tightly closed when not in use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

sodium hydroxide (1310-73-2)		
ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
ACGIH	Remark (ACGIH)	URT, eye, & skin irr
OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³

potassium hydroxide (1310-58-3)		
ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or face shield.

Skin and body protection : Wear suitable protective clothing.

Oven & Grill

Safety Data Sheet

Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. In case of insufficient ventilation, wear suitable respiratory equipment.
Other information	: Do not eat, drink or smoke during use.
Appropriate engineering controls	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Clear amber green
Odor	: Mild
Odor threshold	: No data available
pH	: 13 - 14
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 212 °F
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Vapor pressure	: No data available
Vapor density	: No data available
Specific Gravity @ 77° F	: 1.130 - 1.140
Solubility	: Soluble in water
Partition Coefficient n-Octanol-Water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available

9.2. Other information

VOC content	: No VOC
-------------	----------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with (some) acids: release of heat. Reacts with (some) metals and their compounds: release of highly flammable gases/vapors (hydrogen). Reacts with (some) halogen compounds. Reacts with (strong) oxidizers.

10.2. Chemical stability

Stable under recommended conditions.

10.3. Possibility of hazardous reactions

Reacts vigorously with strong oxidizers and acids. Contact with halogenated compounds may liberate toxic gas.

10.4. Conditions to avoid

Extremely high or low temperatures.

10.5. Incompatible materials

Acids. Oxidizers. May be corrosive to metals.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Nitrogen oxides. Sulfur oxides. Thermal decomposition generates : Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

sodium hydroxide (1310-73-2)	
LD50 dermal rabbit	1350 mg/kg (Rabbit; Literature)
ATE US (dermal)	1350 mg/kg body weight

Oven & Grill

Safety Data Sheet

potassium hydroxide (1310-58-3)	
LD50 oral rat	333 mg/kg (Rat; Equivalent or similar to OECD 425; Experimental value)
ATE US (oral)	333 mg/kg body weight
tetrasodium ethylenediaminetetracetate (64-02-8)	
LD50 oral rat	> 2000 mg/kg (Rat)
ATE US (oral)	500 mg/kg body weight
Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: 13 - 14
Serious eye damage/irritation	: Causes serious eye damage. pH: 13 - 14
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met.
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Corrosion of the upper respiratory tract. Respiratory difficulties.
Symptoms/effects after skin contact	: Causes burns/corrosion of the skin.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed. Abdominal pain. Difficulty in swallowing. Burns to the gastric/intestinal mucosa.

SECTION 12: Ecological information

12.1. Toxicity

sodium hydroxide (1310-73-2)	
LC50 fish 1	45.4 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Solution >=50%)
EC50 Daphnia 1	40.4 mg/l (48 h; Ceriodaphnia sp.; Nominal concentration)
LC50 fish 2	189 mg/l (48 h; Leuciscus idus)
TLM fish 1	99 mg/l (48 h; Lepomis macrochirus)
TLM fish 2	125 ppm (96 h; Gambusia affinis)
potassium hydroxide (1310-58-3)	
LC50 fish 1	> 28.6 mg/l (96 h; Pisces; Lethal)
LC50 fish 2	80 mg/l (Gambusia affinis)
TLM fish 1	80 ppm (24 h; Gambusia affinis)
tetrasodium ethylenediaminetetracetate (64-02-8)	
LC50 fish 1	121 mg/l (96 h; Lepomis macrochirus; Soft water)
EC50 Daphnia 1	625 mg/l (24 h; Daphnia magna)
LC50 fish 2	374 - 792 mg/l (96 h; Lepomis macrochirus; pH > 7)
Threshold limit algae 1	> 100 mg/l (72 h; Scenedesmus subspicatus; Growth)

12.2. Persistence and degradability

sodium hydroxide (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

Oven & Grill

Safety Data Sheet

potassium hydroxide (1310-58-3)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

tetrasodium ethylenediaminetetracetate (64-02-8)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance
Chemical oxygen demand (COD)	0.54 - 0.58 g O ₂ /g substance

12.3. Bioaccumulative potential

sodium hydroxide (1310-73-2)	
Bioaccumulative potential	Bioaccumulation: not applicable.

potassium hydroxide (1310-58-3)	
Bioaccumulative potential	Bioaccumulation: not applicable.

tetrasodium ethylenediaminetetracetate (64-02-8)	
Log Pow	-2.6
Bioaccumulative potential	Bioaccumulation: not applicable.

12.4. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with Local, State, and Federal regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN Number

UN-No.(DOT) : UN3266
Other information : Under 49 CFR 173.154(c) and (b)(1): This product may be shipped as ORM-D or Limited Quantity if the inner packagings do not exceed 1 L (0.3 gallons) or 1.0 kg (2.2 lbs). This provision does not apply to transportation by vessel or aircraft, except where other means of transportation is impracticable.

14.2. UN proper shipping name

Proper Shipping Name (DOT) : UN3266, Corrosive Liquid, Basic, Inorganic, N.O.S. (Sodium Hydroxide, Potassium Hydroxide), 8, PGII
Hazard labels (DOT) : 8 - Corrosive



SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Oven & Grill

Safety Data Sheet

sodium hydroxide (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.
Not subject to reporting requirements of the United States SARA Section 313.
Listed on the Canadian DSL (Domestic Substances List).

RQ (Reportable quantity, section 101(14) of CERCLA as published on EPA's List of Lists) :	1000 lb
---	---------

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

polyethylene glycol mono(octylphenyl) ether phosphate (52623-95-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

potassium hydroxide (1310-58-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.
Not subject to reporting requirements of the United States SARA Section 313.
Listed on the Canadian DSL (Domestic Substances List).

RQ (Reportable quantity, section 101(14) of CERCLA as published on EPA's List of Lists) :	1000 lb
---	---------

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

tetrasodium ethylenediaminetetracetate (64-02-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.
Listed on the Canadian DSL (Domestic Substances List).

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

15.2. International regulations

CANADA

sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List).

potassium hydroxide (1310-58-3)

Listed on the Canadian DSL (Domestic Substances List).

chelant (64-02-8)

Listed on the Canadian DSL (Domestic Substances List).

EU-Regulations

No additional information available.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm.

SECTION 16: Other information

Abbreviations Legend:

H290	May be corrosive to metals
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation
H402	Harmful to aquatic life

Disclaimer

Oven & Grill

Safety Data Sheet

This document is generated for the purpose of distributing health, safety, and environmental data. The information and recommendations are presented in good faith and believed to be from reliable sources, however, the information is provided without any warranty, expressed or implied, regarding its completeness or accuracy. Some information is from sources other than direct test data on the material itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and for this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of the product.

ALL NON-EMERGENCY QUESTIONS SHOULD BE DIRECTED TO CUSTOMER SERVICE 1-(808) 942-2500

Revision date: 08/28/2020 Supersedes: 10/15/2019 Version: 1.2