

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : **Oven Brite**
 Product code : 398

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Concentrated Oven Cleaner

1.3. Details of the supplier of the safety data sheet

Crestek Cleaning Center, Inc.
 1161 Kapiolani Blvd.
 Honolulu, HI 96814
 T 1-(808) 942-2500

1.4. Emergency telephone number

Emergency number : CHEMTEL: 800-255-3924

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Corr. 1B H314
 Eye Dam. 1 H318

Full text of H statements : see section 16

2.2. Label elements

GHS US labelling

Hazard pictograms :



GHS05

Signal word :

Danger

Hazard statements :

Causes severe skin burns and eye damage.
 Causes serious eye damage.

Precautionary statements :

Do not breathe fume, mist, vapors.
 Wash hands and forearms thoroughly after handling.
 Wear eye protection, face protection, protective clothing, protective gloves.
 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Immediately call a POISON CENTER/doctor.
 Specific treatment (see the emergency and first aid section on this label).
 Wash contaminated clothing before reuse.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Hazard not otherwise classified (HNOC)

No additional information available.

2.4. Unknown acute toxicity (GHS US)

1% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
 1% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
 1% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist)).

Oven Brite

Safety Data Sheet

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

(NOTE: If component displays the * (asterisk) symbol, the following statement applies.)

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret.

Full text of H-statements: see section 16

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
2-(2-butoxyethoxy)ethanol	(CAS-No.) 112-34-5	5 - 10	Eye Irrit. 2A, H319
potassium hydroxide	(CAS-No.) 1310-58-3	5 - 10	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318
sodium xylenesulfonate	(CAS-No.) 1300-72-7	5 - 10	Skin Irrit. 2, H315 STOT SE 3, H335
disodium metasilicate	(CAS-No.) 6834-92-0	1 - 5	Skin Corr. 1B, H314 STOT SE 3, H335
Disodium cocoamphodipropionate	(CAS-No.) 68604-71-7	1 - 5	Eye Irrit. 2B, H320
Decyl alcohol, ethoxylated, phosphated	(CAS-No.) 52019-36-0	0.1 - 5	Skin Irrit. 2, H315 Eye Irrit. 2B, H320

(NOTE: If component displays the * (asterisk) symbol, the following statement applies.)

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER/doctor.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Corrosion of the upper respiratory tract. Respiratory difficulties.
Symptoms/effects after skin contact	: Causes burns/corrosion of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed. Abdominal pain. Difficulty in swallowing. Burns to the gastric/intestinal mucosa.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Alcohol-resistant foam. BC powder. Carbon dioxide. Dry chemical powder. Sand/earth.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: DIRECT FIRE HAZARD: Non combustible. INDIRECT FIRE HAZARD: Reactions involving a fire hazard: see "Reactivity Hazard".
Explosion hazard	: INDIRECT EXPLOSION HAZARD: Reactions with explosion hazards: see "Reactivity Hazard".
Reactivity	: Reacts violently with (some) acids: release of heat. Reacts with (some) metals and their compounds: release of highly flammable gases/vapors (hydrogen). Contact with moisture or water may generate heat. Reacts with (some) halogen compounds. Reacts with (strong) oxidizers.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

Oven Brite

Safety Data Sheet

Other information : No additional information available.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

Protective equipment : Protective goggles.
Protective gloves.
Protective clothing.
Respiratory protection.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with appropriate safety equipment.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Plug the leak, cut off the supply. If reacting: dilute toxic gas/vapour with water spray.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Small quantities of liquid spill: neutralize with dilute acid solution. Wash down leftovers with plenty of water. Wash clothing and equipment after handling.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not get in eyes, on skin, or on clothing. Do not breathe fume, mist, vapors. Ensure good ventilation of the work station. Observe normal hygiene standards. Provide good ventilation in process area to prevent formation of vapor. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and forearms thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide local exhaust or general room ventilation. Comply with applicable regulations.

Incompatible products : Acids. Oxidizing agent.

Storage area : Store in a cool, dry well-ventilated area. Keep container tightly closed when not in use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-(2-butoxyethoxy)ethanol (112-34-5)		
ACGIH	ACGIH TWA (ppm)	10 ppm
ACGIH	ACGIH STEL (ppm)	10 ppm

potassium hydroxide (1310-58-3)		
ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Oven Brite

Safety Data Sheet

Eye protection	: Chemical goggles or face shield.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. In case of insufficient ventilation, wear suitable respiratory equipment.
Other information	: Do not eat, drink or smoke during use.
Appropriate engineering controls	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Clear to amber
Odour	: Lemon
Odour threshold	: No data available
pH	: 13 - 14
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °F
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosive limits	: No data available
Vapour pressure	: No data available
Vapor density	: No data available
Specific Gravity @ 77° F	: 1.139 - 1.159
Solubility	: Soluble in water
Partition Coefficient n-Octanol-Water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available

9.2. Other information

VOC content	: < 5 g/l CARB VOC
-------------	--------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with (some) acids: release of heat. Reacts with (some) metals and their compounds: release of highly flammable gases/vapors (hydrogen). Contact with moisture or water may generate heat. Reacts with (some) halogen compounds. Reacts with (strong) oxidizers.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts vigorously with strong oxidizers and acids. Contact with halogenated compounds may liberate toxic gas.

10.4. Conditions to avoid

Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Oxidizers. May be corrosive to metals.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Phosphorus oxides. Sulfur oxides. Nitrogen oxides. Thermal decomposition generates : Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

disodium metasilicate (6834-92-0)

LD50 dermal rat	> 5000 mg/kg bodyweight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
-----------------	---

Oven Brite

Safety Data Sheet

sodium xylenesulfonate (1300-72-7)	
LD50 oral rat	3346 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
ATE US (oral)	3346 mg/kg bodyweight
2-(2-butoxyethoxy)ethanol (112-34-5)	
LD50 oral rat	5660 mg/kg (Rat)
LD50 dermal rabbit	2764 mg/kg (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
ATE US (oral)	5660 mg/kg bodyweight
ATE US (dermal)	2764 mg/kg bodyweight
potassium hydroxide (1310-58-3)	
LD50 oral rat	333 mg/kg (Rat; Equivalent or similar to OECD 425; Experimental value)
ATE US (oral)	333 mg/kg bodyweight

Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: 13 - 14
Serious eye damage/irritation	: Causes serious eye damage. pH: 13 - 14
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met.
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Corrosion of the upper respiratory tract. Respiratory difficulties.
Symptoms/effects after skin contact	: Causes burns/corrosion of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed. Abdominal pain. Difficulty in swallowing. Burns to the gastric/intestinal mucosa.

SECTION 12: Ecological information

12.1. Toxicity

disodium metasilicate (6834-92-0)	
LC50 fish 1	210 mg/l (96 h; Brachydanio rerio)
EC50 Daphnia 1	216 mg/l (96 h; Daphnia magna; Static system)
LC50 fish 2	2320 mg/l (96 h; Gambusia affinis)
EC50 Daphnia 2	632 mg/l (96 h; Lymnaea sp.; Static system)
Threshold limit algae 1	207 mg/l (72 h; Scenedesmus subspicatus; GLP)
sodium xylenesulfonate (1300-72-7)	
LC50 fish 1	> 1580 mg/l (Rainbow trout)
EC50 Daphnia 1	> 1020 mg/l
ErC50 (algae)	758 mg/l
NOEC chronic algae	240 mg/l
2-(2-butoxyethoxy)ethanol (112-34-5)	
LC50 fish 1	1300 mg/l (96 h; Lepomis macrochirus)
LC50 other aquatic organisms 1	10 - 100 mg/l (96 h)
EC50 Daphnia 1	2850 mg/l (24 h; Daphnia magna; GLP)
LC50 fish 2	1805 mg/l (48 h; Leuciscus idus)

Oven Brite

Safety Data Sheet

2-(2-butoxyethoxy)ethanol (112-34-5)	
EC50 Daphnia 2	> 100 mg/l (48 h; Daphnia magna)
TLM fish 1	10 - 100,96 h; Pisces
TLM other aquatic organisms 1	10 - 100,96 h
Threshold limit other aquatic organisms 1	10 - 100,96 h
Threshold limit algae 1	53 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	>= 100 mg/l (96 h; Scenedesmus subspicatus)

potassium hydroxide (1310-58-3)	
LC50 fish 1	> 28.6 mg/l (96 h; Pisces; Lethal)
LC50 fish 2	80 mg/l (Gambusia affinis)
TLM fish 1	80 ppm (24 h; Gambusia affinis)

12.2. Persistence and degradability

disodium metasilicate (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

sodium xylenesulfonate (1300-72-7)	
Persistence and degradability	Biodegradability in water: no data available.

2-(2-butoxyethoxy)ethanol (112-34-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test) data on mobility of the substance available. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.25 g O ₂ /g substance
Chemical oxygen demand (COD)	2.08 g O ₂ /g substance
ThOD	2.173 g O ₂ /g substance
BOD (% of ThOD)	0.11 % ThOD

potassium hydroxide (1310-58-3)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

disodium metasilicate (6834-92-0)	
Bioaccumulative potential	Bioaccumulation: not applicable.

sodium xylenesulfonate (1300-72-7)	
Bioaccumulative potential	No bioaccumulation data available.

2-(2-butoxyethoxy)ethanol (112-34-5)	
BCF fish 1	0.46 (QSAR)
Log Pow	0.56 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

potassium hydroxide (1310-58-3)	
Bioaccumulative potential	Bioaccumulation: not applicable.

12.4. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with Local, State, and Federal regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Oven Brite

Safety Data Sheet

14.1. UN Number

UN-No.(DOT) : UN3266
 Other information : Under 49 CFR 173.154(c) and (b)(1): This product may be shipped as ORM-D or Limited Quantity if the inner packagings do not exceed 1 L (0.3 gallons) or 1.0 kg (2.2 lbs). This provision does not apply to transportation by vessel or aircraft, except where other means of transportation is impracticable.

14.2. UN proper shipping name

Proper Shipping Name (DOT) : UN3266, Corrosive Liquid, Basic, Inorganic, N.O.S. (Potassium Hydroxide, Disodium Metasilicate), 8, PGII
 Hazard labels (DOT) : 8 - Corrosive



SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Disodium cocoamphodipropionate	CAS-No. 68604-71-7	1 - 5%
--------------------------------	--------------------	--------

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-(2-butoxyethoxy)ethanol	CAS-No. 112-34-5	5 - 10%
---------------------------	------------------	---------

disodium metasilicate (6834-92-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.
 Listed on the Canadian DSL (Domestic Substances List).

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

sodium xylenesulfonate (1300-72-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.
 Listed on the Canadian DSL (Domestic Substances List).

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

2-(2-butoxyethoxy)ethanol (112-34-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.
 Subject to reporting requirements of United States SARA Section 313.
 Listed on the Canadian DSL (Domestic Substances List).

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	--

SARA Section 313 - Emission Reporting	1 %
---------------------------------------	-----

Decyl alcohol, ethoxylated, phosphated (52019-36-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	--

potassium hydroxide (1310-58-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.
 Not subject to reporting requirements of the United States SARA Section 313.
 Listed on the Canadian DSL (Domestic Substances List).

RQ (Reportable quantity, section 101(14) of CERCLA as published on EPA's List of Lists) :	1000 lb
---	---------

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

15.2. International regulations

CANADA

disodium metasilicate (6834-92-0)

Listed on the Canadian DSL (Domestic Substances List).

Oven Brite

Safety Data Sheet

proprietary ingredient (1300-72-7)

Listed on the Canadian DSL (Domestic Substances List).

2-(2-butoxyethoxy)ethanol (112-34-5)

Listed on the Canadian DSL (Domestic Substances List).

potassium hydroxide (1310-58-3)

Listed on the Canadian DSL (Domestic Substances List).

EU-Regulations

No additional information available.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

15.3. US State regulations

Prop 65 Disclaimer :

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

SECTION 16: Other information

Abbreviations Legend:

H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H335	May cause respiratory irritation

Disclaimer

This document is generated for the purpose of distributing health, safety, and environmental data. The information and recommendations are presented in good faith and believed to be from reliable sources, however, the information is provided without any warranty, expressed or implied, regarding its completeness or accuracy. Some information is from sources other than direct test data on the material itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and for this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of the product.

ALL NON-EMERGENCY QUESTIONS SHOULD BE DIRECTED TO CUSTOMER SERVICE 1-(808) 942-2500

Revision date: 10/07/2020

Supersedes: 02/27/2020

Version: 1.6