



CITRUS SOLV

NEW & IMPROVED

NATURAL EMULSION CLEANER

DESCRIPTION

CITRUS SOLV IS A BLEND OF NATURAL SOLVENTS, DETERGENTS, AND SURFACTANTS. IT IS DESIGNED TO REMOVE GREASE AND OIL FROM HARD SURFACES, SUCH AS CONCRETE, METAL, AND OTHER HARD SURFACES PAINTED OR UNPAINTED. IT IS A HEAVY DUTY CLEANER THAT WORKS WITHOUT THE USE OF PETROCHEMICAL SOLVENTS, CHLORINATED SOLVENTS, GLYCOL ETHER OR HARD ALKALIS, ACIDS OR OTHER TOXIC CHEMICALS. IT IS SAFE FOR USE ON MOST METALS AND UNPAINTED SURFACES.

CITRUS SOLV HAS A REFRESHING FRAGRANCE, A PLEASANT CHANGE FROM THE STRONG ODORS ASSOCIATED WITH HARSH OR TOXIC SOLVENTS. THIS FRAGRANCE IS NOT A PERFUME BUT THE SCENT OF THE NATURAL SOLVENT.

REGULAR USE WILL KEEP DRAINS CLEAN, DEODORIZED, AND FREE DRAINING. CONTROLS ODOR AROUND SEWAGE TREATMENT PLANTS, DUMPSTERS, AND LANDFILL AREAS WHILE NOT AFFECTING BACTERIAL ACTION.

DIRECTIONS FOR USE

DILUTIONS RATIOS

LIGHT CLEANING: 2 OZ. OF **CITRUS SOLV** PER GALLON OF WATER.

GENERAL CLEANING: 6 TO 8 OZ. **CITRUS SOLV** PER GALLON OF WATER.

HEAVY CLEANING/DEGREASING: 8 TO 12 OZ. **CITRUS SOLV** PER GALLON OF WATER.

CITRUS SOLV MAY BE APPLIED MANUALLY BY A BRUSH, SPONGE, OR MOP. THIS PRODUCT CAN BE APPLIED BY A PRESSURE WASHER IMMERSION TANK. **CITRUS SOLV** CAN BE FOAMED ON FOR LONGER VERTICAL HANG TIME. IT IS SAFE FOR USE ON MOST METALS AND UNPAINTED SURFACES. TEST FOR SAFETY ON PLASTIC AND PAINTED SURFACES.

MANUAL OPERATION: DILUTE CLEANER WITH WATER 4 TO 1 OR UP TO 20 TO 1. WIPE OFF RESIDUE.

PRESSURE SPRAY: DILUTE CLEANER WITH WATER 10 TO 1 OR UP TO 20 TO 1.

TANK IMMERSION: DILUTE CLEANER WITH WATER 4 TO 1 OR UP TO 10 TO 1.

DEODORIZING: ADD 4 OUNCES TO A GALLON OF COLD WATER TO CONTROL ODORS AROUND GARBAGE DISPOSAL AREAS, SEPTIC TANKS, KENNELS, ETC. AROUND SEWAGE PLANTS IT CAN BE APPLIED BY DRIP METHOD OR FOGGING.

DRAIN MAINTENANCE: USE WEEKLY TO KEEP DRAINS AND GREASE TRAPS FREE FLOWING AND SANITARY. POUR 8 OUNCES DOWN DRAIN, LET STAND FOR 10 MINUTES. FLUSH DRAIN WITH HOT WATER. IF DRAIN IS SLOW, REPEAT EVERY 2-3 DAYS UNTIL DRAIN IS FLOWING FREELY. FOR EXTREMELY HEAVY SOILED SURFACES USE AS SUPPLIED OR DILUTE WITH WATER UP TO 3 TO 1.

CARPET CARE DILUTIONS

PORTABLE EXTRACTOR: 2 OZ. PER GALLON OF WATER.

PRE-SPRAY: 3 OZ. PER GALLON OF WATER.

BONNET CLEANER PRE-SPRAY: 3 OZ. PER GALLON OF WATER.

PRECAUTIONS

CONTAINS D'LIMONENE. USE ONLY IN WELL VENTILATED AREA. WEAR NEOPRENE GLOVES WHILE HANDLING THIS PRODUCT. CHEMICAL GOGGLES RECOMMENDED. DO NOT CUT, GRIND, WELD, ETC. NEAR THIS PRODUCT. KEEP OUT OF REACH OF CHILDREN.

PRACTICAL TREATMENTS

EYES: FLUSH EYES WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, OBTAIN MEDICAL ATTENTION.

SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH WATER.

INGESTION: DRINK TWO GLASSES OF WATER. OBTAIN MEDICAL ATTENTION.

INHALATION: REMOVE TO FRESH AIR.

PHYSICAL SPECIFICATIONS

COLOR	CLEAR TO CLEAR YELLOW
FRAGRANCE	CITRUS
PH @ 77°F	10.0 ± 0.5
SPECIFIC GRAVITY	0.970 ± 0.010
VOLATILE ORGANIC COMPOUND (VOC)	245 GM/L

1161 KAPIOLANI BLVD • HONOLULU, HI 96814