



# Diamond Shine

## DESCRIPTION

Diamond-like brilliance, clarity and long lasting performance will save you time and labor, while giving the brilliant appearance you demand on your floors.

### ADVANTAGES

- Designed for ultra-high speed burnishing.
- Flexibility to withstand repeated burnishing without film degradation.
- "Wet look" gloss.
- Exceptional resistance to powdering.
- Long term durability.
- Superior mark resistance.

### WHERE TO USE

**DIAMOND SHINE** is ideally suited for all resilient tile, sealed wood floors, as well as terrazzo and quarry tile found in nursing homes, super markets, shopping centers, industrial, commercial, and institutional facilities. Because of its outstanding wear characteristics, it is recommended for use in schools, offices, hospitals, nursing homes, shopping centers, restaurants, and retail stores.

### DIRECTIONS FOR USE

1. Dust mop and sweep the floor to remove all loose soil.
2. Remove all old wax and floor finish using CRESTEK's **STRIP** with a floor machine and black pad.
3. After pick up of old finish, rinse clean with hot water and use a neutralizer in first rinse. Rinse again.

### MAINTENANCE

1. Maintain by damp mopping as required and dust mopping on a regular basis.
2. Recoat traffic lanes as needed.
3. To enhance gloss in high traffic areas, use CRESTEK's **BUFFY** spray buff using an ultra high speed machine.

### APPLICATION

1. Apply this product with an applicator or finish mop.
2. Let dry 30 to 45 minutes or until tack free.
3. Apply 2 to 3 coats. Floor sealer is not necessary.

**HAZARD STATEMENTS:** Causes serious eye irritation.

**PRECAUTIONARY STATEMENTS:** Wash hands, forearms and face thoroughly after handling. Wear protective clothing, protective clothing, eye protection, face protection. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

### SPECIFICATIONS:

Color.....	White Emulsion
Fragrance.....	Acrylic
pH.....	7.5 – 8.5
Specific Gravity @ 78° F.....	1.022 – 1.042
Film Color .....	Clear
Detergent Resistance .....	Excellent
Drying Time .....	Average of 20 minutes
Stability.....	Minimum 2 years
Coverage .....	1,500 – 2,000 sq. ft./gal.